



Amerex Corporation



Model 600 K 150 LB. HALON 1211 WHEELED FIRE EXTINGUISHER

- Brass, chrome plated operating valve
- 200 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Quick release 50 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Large color coded mylar instruction labels
- Operating temperature range: -65° to +120° F.

| SPECIFICATIONS | 150 LB. HALON 1211 |
|---------------------------------------|------------------------------|
| Model Number | 600 |
| Agent | Halon 1211 |
| U/L Rating | 30A:240B:C |
| Capacity (lbs./kg.) | 150 / 68 |
| Shipping Weight (lb/ kg) | |
| Discharge Time (sec.) | 48 |
| Cylinder - DOT 4BW240 | |
| Operating Pressure | 200 / 1380 |
| Test Pressure | 480 / 3312 |
| Burst Pressre (Minimum) (psi/ kPa) | 960 / 6624 |
| Discharge Range (ft/ m) | 30 - 40 / 9.1 - 12.2 |
| Operating Temp. Range (F/ C) | -65° to +120° / -54° to +49° |
| Safety Disc Burst Range (psi/ kPa) | 400 - 500 / 2760 - 3450 |
| Hose Length (ft./ m) | 50 / 15.2 |
| Hose Diameter (in./ cm) | .75 / 1.90 |
| Wheels (Semi-pneumatic) (in./ cm) | 16 x 4 / 40.64 x 10.16 |
| Height (in./ cm) | 59 / 150.0 |
| Width (in./ cm) | 29 / 73.7 |
| Depth (in./ cm) | 42 / 106.7 |

AMEREX CORPORATION

P.O. BOX 81 ❖ TRUSSVILLE, AL 35173-0081
 Phone: (205) 655-3271 Fax: 1-800-654-5980
 sales@amerex-fire.com www.amerex-fire.com