



Medical and Health Facility Fire Protection

CARBON DIOXIDE is discharged as a white cloud of "snow" which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.

UL Rated: 5B:C

Model: 322NM



5 YEAR WARRANTY

Rust free aluminum cylinders - up to 30% lighter than steel cylinders

Durable High Gloss Polyester Powder Paint

Antiseptic white paint finish (easy to clean)

All Metal Valve Construction

Meets many hospital medical equipment requirements

Independently tested to 7 TESLA and approved for use in MRI facilities

Bar Coded and Bi-lingual Labels

SPECIFICATIONS	CARBON DIOXIDE
Size & Capacity (lbs.)	5
Application	Horn
Model Number	322NM
U/L Rating	5B:C
Shipping Weight (lbs.)	14
Height (in.)	17¾
Width (in.)	8¾
Depth (Diam. - in.)	5¼
Range (ft.)	3- 8
Discharge Time (sec.)	10
F. M. Approved	Yes
Bracket - PN: 17737	NM Wall

NON-MAGNETIC CONSTRUCTION - MRI SAFE

WATER MIST is the ultimate extinguisher for Class A fires and where a potential Class C (electrical) hazard exists. The fine spray from the unique misting nozzle provides safety from electrical shock, greatly enhances the cooling and soaking characteristics of the agent and reduces scattering of burning materials. The Amerex Water Mist extinguishers contain de-ionized water making them the best extinguishers for protection of hospital environments, valuable books and documents, telecommunication facilities and "clean room" manufacturing facilities. The Amerex Water Mist extinguishers are easy to use, maintain, and service.

5 YEAR WARRANTY

RUGGED

Stainless Steel Cylinders
Durable High Gloss Polyester Powder Paint
Antiseptic white paint finish (easy to clean)
All Metal Valve Construction
Exclusive crevice free, butt welded cylinder

ENVIRONMENTALLY FRIENDLY

No O.D.P. (Ozone Depletion Potential)
No EPA phase out or restrictions
No global warming concerns
Independently tested to 7 TESLA and approved for use in MRI facilities

CLEAN

Causes no respiratory problems
De-ionized water extinguishing agent (sold separately)
No powder residue

USER FRIENDLY

Wand provides greatest operator safety
Maximum visibility during discharge
No electrical conductivity back to the operator
No thermal or static shock
Minimal training - simplest to use
Most economical agent available
Bar Coded and Bi-lingual Labels

UL Rated: 2A:C

Models: B272NM
B270NM



SPECIFICATIONS	WATER MIST	
	Hose and Wand	Hose and Wand
Application	Hose and Wand	Hose and Wand
Agent	DE-IONIZED WATER	
Model Number	B270NM	B272NM
U/L Rating	2A:C	2A:C
Capacity (gals.)	1.8	2.5
Shipping Wt. (lbs.) (Empty)	7	8
Extinguisher Height (in.)	18½	24½
Height with Hose & Wand [Installed in Clips] (in.)	24½	27½
Width with Hose & Wand [Installed in Clips] (in.)	11	11
Depth (Diam. - in.)	7	7
Range (ft.)	10-12	10 - 12
Discharge Time (sec.)	72	80
Bracket - PN: 14315	NM Wall	NM Wall



Amerex Corporation

P.O. Box 81 ♦ Trussville, AL 35173
Ph: (205) 655-3271 ♦ Fax: 1-800-654-5980
inquiries@amerex-fire.com
www.amerex-fire.com